



TEGERA® 35

Leather glove, half-lined, 1,2 - 1,4 mm split cowhide, cotton, jersey, Cat. II, yellow, grey, reinforced index finger, reinforced fingers and thumb, elasticated 180°, for heavy work

PROPERTIES

High level of protection

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Split cowhide

PALM THICKNESS 1,2 - 1,4 mm

BACK MATERIAL Cotton, Split cowhide

LINING Half-lined

LINING MATERIAL Jersey

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 240-270 mm

COLOUR Yellow, grey

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, cotton, natural latex

INNER MATERIAL SPECIFICATION Cotton

SIZE	ART. NO.	EAN NO.
8	35-8	7392626003576
10	35-10	7392626003590
9	35-9	7392626013124
11	35-11	7392626013131

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 35

FEATURES

Reinforced index finger, reinforced fingers and thumb

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY AREAS OF USE

Engineering, transport work, mining

PRIMARY INDUSTRIES OF USE

Automotive, transportation

TYPE OF WORK

Heavy weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3213X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 35

EU-TYPE EXAMINATION

0493 Centexbel, Technologiepark 70, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 < 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3213X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com